

**Siphonic urinal
LEMA
84019.7**



TECHNICAL DATA

Order no.	84019.7	Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89900.7
Certified to	DIN 1390, EN 13407		LIS SMART CONTROL-U horizontal inlet connection, order no. 89418.9
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4		1-liter spare part siphon, order no. 89419.6
	LIS SMART CONTROL-U, order no. 37066.0		Stone screw fixing set M8
Specification	1-l flushing siphonic urinal		Adaption set for stone screws M10, order no. 89281.6
	Ceramic siphon cover		Adaption set for stone screws M12, order no. 89281.4
	Siphon replaceable without dismantling urinal only in combination with fixing set order no. 89280.8		
	Charge 000 – DN 40	Colours	see colour table
	Charge 401 – DN 50	SPECIFICATION TEXT	
Water inlet	concealed 1/2"	Siphonic urinal Laufen-LEMA, sanitary ceramic	
Outlet	horizontal	DIN 1390, EN 13407, dimensions 350 x 400 x 700 mm	
Flushing	minimum 0.5 l - 3.0 l	minimum 0.5 l - 3.0 l flush, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal, flushing rate minimum 0.3 l/s	
Flushing rate	minimum 0.3 l/s	siphon replaceable without dismantling urinal,	
Weight	24,5 kg	Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)	
Mounting acc. incl.	Ceramic siphon cover, order no. 89818.9	Further options / accessories: LIS horizontal inlet connection, 1-liter spare part siphon, LIS CU2 concealed frame for urinal without integrated control or LIS SMART CONTROL-U concealed kit for urinal flash control and front plate with infrared sensor	
	Wall fixing set M8 LAUFEN, order no. 89280.8	Order no. 84019.7	
	1-liter siphon, order no. 89419.3		
	Charge 000 – waste connection pipe DN 40, order no. 89419.4		
	Charge 401 – waste connection pipe DN 50, order no. 89419.5		

TECHNICAL DRAWINGS / S 1 : 20

